

DS-D4239RO-CA P3.9 Outdoor Rental LED Display













刷新率3840 具备面罩 航指

DS-D4439RO-CA is the new generation indoor full-color rental LED display. LED display features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as Stage performances, hotel weddings, festival celebrations, exhibitions, etc.

- Excellent in precision, heat dissipation, toughness, and solidity with the die-casting aluminum cabinet design.
- 500 mm × 500 mm cabinet with multiple dot pitches available and both indoor and outdoor scenarios applicable.
- Front maintenance available with the magnetic suction design, and quick front maintenance and installation achievable with the fixed installation of module at any position.
- 10-seconds replacement achievable with power supply, display controller, and adapter board integrated.
- Fast locking from the top, bottom, left, and right;
 2-seconds locking for adjacent cabinets; convenient wiring with aviation plugs.
- Pendant mounting and standing available for installation.
- Free of fans and noise with excellent heat dissipation.
- High refresh rate (up to 3840 Hz) and high grey scale.





Specification

Model		DS-D4239RO-CA
	Pixel	SMD Triad LED
	Configuration	
	Pixel Pitch Category	P3.9
	Pixel Pitch	3.906 mm
	Lamp Dimensions	1.9 × 2.1 mm
	Modules Component	2 × 2
	Dimensions (W × H × D)	500 mm × 500mm × 87 mm (19.69" × 19.69" × 3.43")
	Resolution	128 × 128
Cabinet	Area	0.25 m ²
	Weight	8.5 Kg (18.74lb)
	Pixel Density	65536 dots/m ²
	Lamp Board Housing	with housing
	Cabinet Material	Die-cast aluminum
	Maintenance Method	Front maintenance
	Cabinet Flatness	0.2 mm
	Protection Level	IP54
Key Material	Lamp Encapsulation	NationStar 1921
	Driver IC	ICN2153
	Control System	DS-D42C06-N
Display	White Balance Brightness	5000 cd/m ²
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 6000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥97%
Processing Performance	Driving Method	Constant current driving



	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz
	Grey Level	16 bit
	Display Color	281 trillion
Power	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 680 W/m²
	Average Consumption	≤ 230 W/m²
Working Environment	Working Temperature	-15-50 ℃
	Working Humidity	10%~85%RH
	Storage Humidity	10%~85%RH
	Storage Temperature	-20~60 ℃
General	Gross Weight	85 Kg (187.4 lb)
	Package Dimension (W × H × D)	560 mm × 580 mm × 670 mm (6 IN 1)
	Lifespan	Lamp 100,000 hours

Available Model

DS-D4239RO-CA(海外标配),

- Accessory
- Optional









Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com